

Technical Data Sheet

AF-193

Ingredient Hydrocarbons, inorganic carriers

Warranty 12 months (kept in a cool, dry place at room temperature)

Applications AF-193 is used in

- Dry mortar
- Gypsum precast panels
- Dry powder coating
- Internal and external wall putty

Features ● Good degassing performance

● Good anti-foaming and anti-foaming performance

● The product has good fluidity and is easy to use.

Physical indicators

Exterior white solid powder

pH value 4.0-8.0

Density 0.3-0.7g/cm³

Instructions ● Add directly for use, not suitable for dilution.

- Adding amount 0.1%~1%
- The optimal addition amount is determined according to the actual situation on site

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away from direct sunlight
- Refer to the product' s Material Safety Data Sheet (MSDS) before use

Usage

- Not for human injection

restrictions

- This product is not tested or represented as suitable for medical or pharmaceutical use

Package

- 15 kg bag
-

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.