

Technical Data Sheet

AF-744

Ingredient	Mineral oil and hydrophobic particles
-------------------	---------------------------------------

Warranty	6 months (kept in a cool, dry place at room temperature)
-----------------	--

Applications	AF-744 is used in <ul style="list-style-type: none">● Water-based ink● Emulsion polymerization
---------------------	---

Features	<ul style="list-style-type: none">● Fast defoaming and long-lasting defoaming● Good dispersion and compatibility in the system● Long-term storage stability, no stratification
-----------------	--

Physical indicators	
Exterior	Milky white to pale yellow cloudy liquid
pH value	5.0-7.0
Viscosity, 25°C	300-1200mPa.s

Instructions	<ul style="list-style-type: none">● Add when mixing ink or printing later.● The addition amount is generally 0.1~1%, and the optimal addition amount is adjusted according to the actual situation on site.
---------------------	--

Precautions	<ul style="list-style-type: none">● There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water● Storage at room temperature (5-40°C), away from direct sunlight● Refer to the product's Material Safety Data Sheet (MSDS) before use
Usage	<ul style="list-style-type: none">● Not for human injection
restrictions	<ul style="list-style-type: none">● This product is not tested or represented as suitable for medical or pharmaceutical use
Package	<ul style="list-style-type: none">● 25kg/50kg/180kg plastic drum or 850kg IBC drum

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.