

Technical Data Sheet

AF-712

Ingredient Fatty acid esters

Warranty 12 months (kept in a cool, dry place at room temperature)

Applications AF-712 is used in

- Landfill leachate.
-

Features

- The product has outstanding anti-foaming performance
- It has strong applicability, and its fluctuations in water quality have little impact on product performance

Physical indicators

Exterior Yellow or brown liquid

pH value 6.0-9.0

Viscosity, 25°C <1000mPa.s

Instructions

- It can be added directly for use and dilution is not recommended.
- The addition amount is generally 100~1000ppm. The optimal addition amount is determined according to the actual

situation on site.

- The adding point is generally a place where the foam is rich and the defoaming agent is easily dispersed.

Precautions

- There are no fatal or harmful ingredients to the human body, but try not to touch it directly or use it if it accidentally gets into the eyes, rinse with clean water
- Storage at room temperature (5-40°C), away from direct sunlight
- Refer to the product's Material Safety Data Sheet (MSDS) before use

Usage

- Not for human injection

restrictions

- This product is not tested or represented as suitable for medical or pharmaceutical use

Package

- 25kg/200kg plastic drum or 1000kg IBC drum
-

LIMITED WARRANTY INFORMATION - PLEASE READ CAREFULLY

The information provided here is believed to be accurate and in good faith. However, because conditions and methods of use of our products are beyond our control, this information should not substitute for customer's testing to ensure that our products are safe, effective, and fully satisfactory for their intended use. Suggestions for use shall not be construed as grounds for infringement of any patent rights.